

型号	冷却能力 Kcal/h	主机进出口径 mm	喷淋泵		风机		外形尺寸（两组尺寸分别为主机，辅机）			主机质量 Kg	运行质量 Kg
			水量 m ³ /h	功率 KW	风量 m ³ /h	功率 kw	长 (L) mm	宽 (w) mm	高 (H) mm		
XENBL-6T	30000	DN50	14.4	0.75	12300	0.55	2300	1050	2500	320	610
XENBL-10T	50000	DN50	14.4	0.75	16080	0.75	2300	1050	2500	430	750
XENBL-15T	75000	DN65	14.4	0.75	24600	0.55x2	3300	1030	2500	550	920
XENBL-20T	100000	DN65	14.4	0.75	24600	0.55x2	3300	1030	2500	680	1020
XENBL-30T	150000	DN65	45	1.5	32160	0.75x2	3400	1130	2500	750	1350
XENBL-40T	200000	DN80	45	1.5	43480	1.1x2	3400	1130	2600	820	1900
XENBL-50T	250000	DN80	45	1.5	43480	1.1x2	3500	1400	2600	1060	2200
XENBL-60T	300000	DN80	45	1.5	54000	1.5x2	3500	1400	2600	1150	2600
XENBL-70T	350000	DN80	58	2.2	54000	1.5x2	3500	1720	2600	1280	2800
XENBL-80T	400000	DN80	58	2.2	69000	2.2x2	3500	1720	2600	1400	3050
XENBL-90T	450000	DN100	58	2.2	69000	2.2x2	3700	1900	2600	1700	4100
XENBL-100T	500000	DN100	58	2.2	108000	1.5x4	2700	2380	2650	1860	5800
							1200	2000	2000		
XENBL-120T	600000	DN125	100	3	108000	1.5x4	2820	2380	2650	2100	6500
							1200	2000	2000		
XENBL-150T	750000	DN125	100	3	111000	2.2x3	3400	2380	2650	2400	6900
							1800	2200	2000		
XENBL-200T	1000000	DN200	100	3	216000	2.2x6	4200	2380	2650	3800	8800
							1800	2800	2000		
XENBL-250T	1250000	DN200	100	3	226000	2.2x8	6000	2380	2700	4500	9000
							2000	2200	2000		
XENBL-300T	1500000	DN200	200	6	339000	5.5x4	6400	2380	2700	4900	9200
							2200	2400	2000		